



स० 441

नई बिल्ली, शनिवार, अक्तुबर 30, 1993 (कार्तिक 8, 1915)

病气气(图:34)

STERED NO. DL-33061/93

No. 44]

NEW DELHI, SATURDAY, OCTOBER 30, 1993 (KARTIKA 8, 1915)

इस माग में भिन्न पुष्ठ संख्या दी जाती है जिससे कि यह अलग संकलन के रूप में रखा जा सके [Separate paging is given to this Part in order that it may be filed as a separate compilation]

भाग III—खण्ड 2 [PART III—SECTION 2]

पेटेन्ट फार्यालय द्वारा जारी की गई पेटेन्टों और हिजाइनों से सम्फन्धित अधिसूचनाएं और नोटिस [Notifications and Notices Issued by the Patent Office relating to Patents and Designs]

THE PATENT OFFICE

PATENTS AND DESIGNS

Calcutta the 30th October 1993

ADDRESS AND JURISDICTION OF OFFICES OF THE PATENT OFFICE

The Patent Office has its Head Office at Calcutta and Branch Offices at Bombay, Delhi and Madras having territorial Jurisdiction on a zonal basis as shown below :--

Patent Office Branch, Todi Estates, III Floor, Lower Parel (West), Bombay-400 013.

The States of Gujarat, Maharashtra and Madhya Pradesh and the Union Territories of Goa, Daman and Diu and Dadra and Nagar Haveli.

Telegraphic address "PATOFFICE".

Patent Office Branch, Unit No. 401 to 405, III Floor, Municipal Market Building, Saraswati Marg, Karol Bagh, New Delhi-110 005.

The States of Haryana, Himachal Pradesh, Jammu Kashmir, Punjab, Rajasthan and Uttar Pradesh and the Union Territories of Chandigarh and Delhi.

Telegraphic address "PATENTOFIC".

Patent Office Branch, 61, Wallajah Road, Madras-600 002.

The States of Andhra Pradesh, Karnataka, Kerala, Tamilnadu and the Union Territories of Pondicherry, Laccadive, Minicoy and Aminidivi Islands.

Telegraphic address "PATENTOFIS".

Patent Office (Head Office), "NIZAM PALACE", 2nd M.S.O Building, 5th, 6th and 7th Floor, 234/4, Acharya Jagadish Bose Road, Calcutta-700 020.

Rest of India.

Telegraphic address "PATENTS".

All applications, notices statements or other decuments or any fees required by the Patents Act, 1970 or the Patents Rules, 1972 will be received only at the appropriate Offices of the Patent Office.

Fees:—The fees may either be paid in cash or may be sent by Money Order payable to the Controller at the apropriate Offices or by bank draft or cheque, payable to the Controller drawn on a scheduled bank at the place where the appropriate office is situated.

पेट ट कार्यालय

एकस्व तथा मिकस्प

कलकत्ता, विनांक 30 अक्तूबर 1993

पेट ट कार्यालय के कार्यालयों के पते एवं क्षेत्राधिकार

पैटीट कार्यालय का प्रधान कार्यालय कलकते में अवस्थित है सथा अम्बर्ड, दिल्ली एवं सदास में इसकों शाखा कार्यालय हं, जिनकों प्राविधिक क्षेत्राधिकार जॉन के आधार पर निम्न रूप में प्रविधित हैं:—

पेटाँट कार्यालय शासा, टोंडी इस्टेंट, शीसरा तल, लोअर परेल (पहिचम), एम्बर्ड-400013 ।

गुजरात, महाराष्ट्र तथा मध्य प्रदेश राज्य क्षेत्र एवं संघ शासित क्षेत्र गोजा, वर्मन तथा दीव एवं दादरा और नगर हयेली ।

तार पता--"पटाॅरिफसे"

पेटांट कार्यालय शाखा, एकक सं. 401 से 405, तीमरा तल, मशरपालिका बाजार भवन, सरस्वती मार्ग, करोल बान, नहीं दिल्ली-110005 ।

हरियाणा, हिमाचल ५ देश. जम्मू तथा कश्मीर, पंजाब, राजस्थान तथा उत्तर प्रदेश राज्य क्षेत्री एवं संघ दाशित क्षेत्र चंडीगढ़ तथा दिल्ली ।

तार पता---''पेटेंटोफिक''

पेटांट कार्यालय साचा, 61, बालाजाह रोड, मदास-600002 ।

बान्ध् प्रवेश, कर्नाटक, करेल, तमिलनाड राज्य क्षेत्र एवं संघ शासित क्षेत्र पाण्डिकोरी, लक्षव्यीप, मिनिकाय तथा एमिनिदिवि द्वीप ।

तार पता--"पेट टांफिस"

पेटोट कार्यालय (प्रधान कार्यालय), निजाम पैलेस, दिवतीय बहुत्तलीय कार्यालय, भवन 5, 6 तथा 7वां तल, 234/4, काचार्य जगदीश बोस रोड, अलकसा-700020 ।

भारत का अवशेष क्षेत्र ।

तार पता—"पट**ेहस"**

पेटांट अधिनियम, 1970 या पेटांट नियम, 1972 में अपे-किस सभी आवेदन-५त्र, सूचनाएं, विवरण या छन्य प्रलेख पेटांट कार्यांचय के केवल उपयुक्त कार्यांचय में ही प्राप्त किए आएंगे।

श्रुत्क :— श्रुत्कों की बदायगी या तो नकत की आएगी अथवा छप्युक्त कार्यालय में नियंत्रक की भूगतान योग्य धनाव के अथवा डाक बाव के या जहां उपयुक्त कार्यालय अवस्थित हैं; उस स्थान के अनुसूचित बैंक से नियंत्रक की भूगतान योग्य बैंक डाप्ट अथवा चैक व्वारा की जा सकती है।

CORRIGENDA

In the Gazette of India Part III, Section 2.

- (a) Dated the 14th March, 1992, page-317, Col. 2, for Patent No. 753/Mas/87 filed on 19th October, 1987 read the applicants as THE ENGLISH ELECTRIC COMPANY OF INDIA LIMITFD.
- (b) Dated the 28th March, 1992, page-385, Col. 2, for application for Patent No. 121/Del/87 filed on 13th February 1987 read the accepted No. as 170464 instead the 170264.
- (c) In page 392. col. 2, for application for Patent No 119/Bom/89 filed on may 5, 1989 read the applicant as ELCOR CORPORATION instead of ELLOR CORPORATION.
- (d) In page-393, col 2, for application for Patent No. 147/Bom/89 filed on 7th June. 1989 read the applicants as BARMAG AG, instead of BARMAG A.C.
- (e) Dated the 4th April 1992, page-416, col. 2, for application for Patent No. 906/Mas/87 filed on 17th December. 1987 read the accepted No. as 170514.
- (f) In page-418, col. 1 for application for Patent No. 935/Mas/87 filed on 28th December, 1987 read the applicants as BASF AKTIENGESELLSCHAFT instead of BASF AKTIENGESCHAFT.
- (g) Dated the 11th April, 1992, page-461, col. 2, for application for Patent No. 269/Mas/90 filed on 11th April, 1990 read the applicants as TAKEDA CHEMICAL

INDUSTRIES, LTD., instead of TAKEDA CHEMICAL INDUSTRIES LTD.

- (h) Dated the 18th April, 1992, page-482, col. 1, for application for Patent No. 1142/Del/87 filed on 29th December, 1987 read the applicants as SAMHWA ELECTRIC INDUSTRIAL Co. instead of SAMHWA ELECTIR INDUSTRIAL Co.
- (i) Dated the 9th May, 1992, page-601, col. 2, for application for Patent No. 516/Cal/88 filed on 24th June, 1988 read the First applicants as MITSUI TOATSU CHEMICALS INCORPORATED instead of MITSUI OATSU CHEMICALS INCORPORATED.
- (j) In page 605, col. 2. for application for Patent No. 126/Cal/89 filed on 13th February. 1989 read the applicants AEROSPATIALE SOCIETE NATIONALE INDUSTRIFULE instead of AEROSPATIATLE SOCIETE NATIONALE NATIONALE INDUSTRIFULE
- (k) In page-611, col. 1. for application for Patent No. 447/Del/87 filed on 25th May, 1987 read the accepted No. as 170736 instead of 710736.
- (1) In page-609, col. 2, for application for Patent No. 427/Dcl/87 filed on 15th May. 1987 read the applicants as THE PIFSSFY COMPANY PLC. instead of THE POLESSEY COMPANY PLC.
- (m) Dated the 6th June. 1992. Page-694. col. 1, for application for Patent No. 193/Mos/88 filed on 25th March, 1988 read the applicants as HYDRO-QUEBE.C.

APPLICATIONS FOR PATENTS FILED AT THE HEAD OFFICE

AT 234/4, ACHARYA JAGADISH BOSE ROAD, CALCUTTA-20.

The dates shown in the crescent brackets are the dates claimed under section-135, of the patents act, 1970.

Calcutta-20, the 7th September 1993

- 519/Cal/93 Lunkalapalli Gopala Rao. Double Filament, Multi-watt GLS Lamp.
- 520/Cai/93 Dr. Subrata Pal, Dr. A. Pal & Dr. T. K. Pal. Hydroxyapatite Coated Titanium Dental Implant for single tooth replacement.
- 521/Cal/93 Norton Healthcare Limited. Medicament Dispensing device. Convention No. 9218937.2; filed on 8-9-1993. Great Britain.
- 522/Cal/93 Norton Healthcare Limited. Medicament Dispensing Device. (Convention Nos. 9218937.2, 9225389.7; filed on 8-9-92 and 4-12-92; Great Bruain).

08th September, 1993

- 523 / Cal/93 Johann Berger. Textile Hollow Body Method of producing it.
- 524/Cal/93 (1) Robert Douglas, (2) Benjamin Earl Bulkley, (3) Dale Eugene Laplante, (4) James Martin Anderton Askey, (5) Alam Granville Jones, and (6) Charles Earl Cooper. Electronic Fuel Injection system for large compression ignition engine.
- 525/Cal/93 Henri E. Rosen, Shees capable of accommodating and fitting different foot widths, (divided out of No. 669/Cal/89; amediated to 16-8-1989).
- 526/Cal/93 Tatsuo Ono. Form Panel.
- 527/Cal/93 Brojo Renu Ganguly, Hi Life Railway Turnout.
- 528/Cal/93 Brojo Renu Ganguly, Hi Life Railway Turnout.

10th September, 1993

- 529/Cal/93 Santanu Roy. A Novel Process for making polymeric intermediates and wood-like products made therefrom.
- 530/Cal/93 Commonwealth Scientific and Industrial Research Organisation. Method for the storage of Entomorathogenic Nematodes. (Convention No. PL4791/92 filed on 10-9-92. Australia.)
- 531/Cal/93 Hamatech Halbleter-Maschinenbau Und Technologie GmbH. Device for coating substrates in semiconductor production.
- 532/Cal/93 Sri Usha Shankar Bhattacharya. A 3-Step control, higher power wick stove.
- Applications for Patents filed in the Patent Office Branch at Todi Estates, Illrd Floor, Sun Mill Compound, Lower Parel (W), Bombay-13.

10th August 1993

246/Bom/93 Taraprakash Prabhakar Vartak. A process for higher recovery of sugar from sugarcane.

11th August 1993

247/Bom/93 Dr. Rashmikant Shantilal Parikh. Improvement in or related to setting of polyester fibres, filaments fabrics of 100% polyester or its blends with natural and/or other synthetic fibres.

12th August 1993

- 248/Bom/93 Nichrome Metal Works Pct. Ltd. A device for delivering a pre-determined continuous length chain of pouch means.
- 249/Bom/93 Nevrekar Venkatesh R. Self-aligning sealing member for valve assembly.

13th August 1993

250/Bom/93 Scitech Centres. A process for preparing lyophilised rumen liquor capsule for ruminant animals

16th August 1993

- 251/Bom/93 Ahmedabad Textile Industry's Research Association. A cell type air humidification system for industrial purpose.
- 252/Bom/93 Prashant Manohar Oak A device to control upper and lower levels in an ash shurry tank.
- 253/Bom. 93 Hindustan Lever Ltd. Polymeric anticalculus agents.
- 254/Bom/93 Trigon Metal Sections Pvt, Ltd. Structural angles for making structures.

17th August 1993

- 255/Bom/93 Harivadan Lallubhai Parikh Voltage stabilizer.
- 256/Bom/93 Harivadan Lallubhai Parikh. Electronic circuit for automatic voltage stabilizer.

18th August 1993

- 257/Bom/93 Augustine Henry Shelke. Improved table and padestal fan.
- 258/Bom/93 Mrs. Ashruffali Aziz Dharamsey & Others.
 Pilfer Proof display device for compact discs/
 laser vision discs audio and video tapes and the like.

19th August 1993

- 259/Bom/93 Praj Industries Ltd. A process to carry out continuous ethanol fermentation using floculating yeast and yeast recycle involving acidification of the yeast cream for controlling bacterial contamination and its activity before yeast cream recycle simultaneously.
- 260/Bom/93 Ashok Dongre. A selective message communication apparatus.

23rd August 1993

261/Bom/93 Rathin Sinha. A cutting and gripping device.

24th August 1993

- 262/Bom/93 Govind Sadashive Bapat. The way of constructing the body of a tanker-cum-truck.
- 263/Bom/93 Prof. Dr. Heeresh Chandra. Chandra R. shutters.
- 264/Bom/93 Hindustan Lever Ltd. U. K. Priority dt. 25-8-92 & 5-11-92. Liquid cleaning compositions comprising primary alkyl sulphate and non-ionic surfactants.
- 265/Bom/93 Raymon Nogueira & others. Equipments of filteration.

25th August 1993

- 266/Bom/93 Scitech Centre. A herbal based galactogogue capsule for dairy animals and a process for preparing the same.
- 267/Bom/93 Scitech Centre. A feed supplement capsule for improving quality and quantity of milk and general condition of ruminant animals and a process for preparing the same.
- 268/Bom/93 Rama Vishwakarma & others. Pawan Automotive Engine.
- 269/Bom/93 Kemp & Company Ltd. A mechanical height adjustment device for chair.

26th August 1993

270/Bom/93 Sanjaya Maniktala & Others. Protection for electronic ballasts for gas discharge fluorescent lamps

- 271/Bom/93 Sanjava Maniktala & others. Improved switching regulator.
- 272/Bom/93 Das Ram Krishna. Theory, working mechanism & designing of Ramjantrao.

27 August 1993

2/3/Bom/93 Mahendra Vasant Sapre. A device to accomplish infinitely variable rate of actuation in the electrically driven servo controlled actuators.

Applications for Patents filed at the Patent Office Branch, 61, Wallajah Road, Madras-600 0002.

30th August 1993

- 610/Mas/93 Ravindranath Damodaran. Integrated personal satellite TV system.
- 611/Mas/93 Seshagiri Rao B. Y. Osmotic pressure pumping process.
- 612/Mas/93 S. V. Murthy. Automobile wind shield automatic wiping system.
- 613/Mas/93 Davstar California, Inc. Integral centrifuge tube and specimen slide.
- 614/Mas/93 Ernest Robert Bodnar. Roll formed metal member with reinforcement indentations. (September 2, 1992; Canada).

1st September 1993

- 615/Mas/93 G. Johnson. Johnson thief detector for vehicles.
- 616/Mas/93 G. Johnson. Johnson vertical meter for vehicles.
- 617/Mas/93 Liquid Carbonic Corporation. Method and apparatus for determining the solid fraction of a stored cryogenic refrigeration system.
- 618/Mas/93 Rosemount Inc. Vortex Flometer.
- 619/Mas/93 Klockner-Humboldt-Deutz AG, Multiengine system with supercharged diesel internal-combustion engines.
- 620/Mas/93 Takata Corporation. Structure for mounting a lid of an air bag device for use in a passenger's seat.
- 621/Mas/93 Mac Lean-Fogg Company. Insulator structure and method of construction.
- 622/Mas/93 Narayana Thevar Sabapathy. A device for automatic operation of clutch in automobiles having vonventional gear changing mechanism.
- 623/Mas 93 Andre Viozat, S. Lalitha & K. Jatalakshmi. A device for automatic control of the operation of a furnace.

2nd September 1993

- 624/Mas/93 Multiclip Company Limited. Securing Device. (September 4, 1992; United Kingdom).
- 625/Mas/93 Palitex Project-Company GmbH. Multi-station textile machine, especially double (wisting machine or cabling machine, with sequentially arranged spool containers.

3rd September 1993

- 626/Mas/93 P. Radhakrishnan. Thermal efficient internal combustion engine.
- 627/Mas/93 Monsanto Company. Process for preparing isocyanates.
- 628/Mas/93 Monsanto Company. Preparation of urethane and carbonate products.
- 629/Mas/93 Andries Johannes Du Precz and Smuts Du Precz.

 Building construction and building element for use therewith.
- 630/Mas/93 N. V. Raychem S. A. Environmental scaling. (September 4, 1992; Great Britain).

ALTERATION OF DATE UNDER SECTION-16
Patent No. 172650 (33/M/91) Ante-dated to 7th April, 1987.

COMPLETE SPECIFICATION ACCEPTED

Notice is hereby given that any person interested in opposing the grant of patents on any of the Applications concerned, may, at any time within four months of the date of this issue or within such further period not exceeding one month applied for on Form 14 prescribed under the Patents Rules, 1972 before the expiry of the said period of four months, given notice to the Controller of Patents at the appropriate office on the prescribed Form 15, of such opposition. The written statement of opposition should be filed alongwith the said notice or within one month of its date as prescribed in Rule 36 of the Patents Rules, 1972.

The classifications given below in respect of each specification are according to Indian Classification and International Classification.

Typed or photo copies of the specifications together with photo copies of the drawings, if any, can be supplied by the Patent Office, Calcutta or the appropriate Branch Office on payment of the prescribed copying charges which may be ascertained on application to that office. Photo copying charges may be calculated by adding the number of pages in the specification and drawing sheets mentioned below against each accepted specification and multiplying the same by two to get the charges as the copying charges per page are Rs. 2/-.

स्थीनृत सम्पूर्ण विनिद^भश

एनव्व्यारा यह सूचना वी जाती है कि सम्बद्ध आवेवनों में से किसी पर पेटेंट अनुवान का विरोध करने के इच्छुक कोई व्यक्ति, इसके निर्मम की तिथि से चार (4) महीने या अग्रिम एसी अविध जो उक्त 4 महीने की अविध की समाप्ति के पूर्व पेटेंट नियम, 1972 के तहत विहित प्रपत्र 14 पर आवेदित एक महीने की अविध से अधिक तहां, के भीतर कभी भी नियंत्रक, एकस्व की उपयुक्त कार्यालय को एसे विरोध की सूचना विहित प्रपत्र 15 पर वे सकते हैं। विरोध सम्बन्धी लिखित वक्तव्य, उक्त सूचना के साथ अथवा पेटेंट रियम, 1972 के नियंत्र 36 में यथा विहित इसकी विधि के एक महीने के भीतर ही फाइल किए जाने चाहिए।

''प्रत्येक विनिवर्षेत्र के संदर्भ में नीच विए वर्गीकरण, भार-तीय वर्गीकरण तथा अन्तरराष्ट्रीय वर्गीकरण के अनुरूप हैं।''

क्यांकन (चित्र बारेखों) की फोटो प्रतियां यदि कोई हो, के साथ विनिव्दें को टेकिस अथवा फोटो प्रतियों की अपूर्ण पेटेंट कार्यालय, कलंकसा अथवा उपयुक्त शाखा कार्यालय व्वारा विहित लिप्यालारण प्रभार जिसे उक्स कार्यालय से पत्र-व्यवहार द्वारा सुनिश्चित करने के उपरांश उसकी अवायगी पर की जा मकी है । विनिव्देंश की गृष्ठ गंग्या के साथ प्रत्येक स्वीकृत विनिव्देश के सामने नीचे विणित चित्र आरोब कांगजीं को जोड़कर उसे 2 से गृणा करके; (क्योंकि प्रत्येक पृष्ठ का सिप्यान्तरण प्रभाव 2/- रा. को फोटो लिप्याल्यरण प्रभार का परिकलन किया जा सकता है।

Ind. Cl.: 32E. [IX(I)] 155 F2 (XXIII)

172621

Int. Cl.: C08J 5/00, 5/12.

A PROCESS FOR THE PREPARATION OF AN ARTICLE COATED WITH A POLYMERIC MATERIAL.

Applicant: EXXON RESEARCH AND ENGINEERING COMPANY, A CORPORATION ORGANISED UNDER THE LAWS OF THE STATE OF DELAWARE, UNITED STATES OF AMERICA OF 180 PARK AVENUE, FLORHAM PARK, NEW JERSEY 07932. UNITED STATES OF AMERICA.

Inventor(s): PACIFICO VIERNES MANALASTAS, WAR-REN ALAN THALER, EVELYN NOBLES DRAKE & ISRAEL SZABSAI PASTERNAK.

Application for Patent No. 370/Del/87 filed on 28 April 1987.

Appropriate Offic for opposition proceedings (Rule 4, Patent Rule 1972), Patent Office Branch New Delhi-5.

12 Claims

A process for preparing article such as herein described said process comprises coating at least one surface of substrate of the kind such as herein described with a polymeric coating having a thickness of 1 to 100 micrometers said polymeric coating comprises a neutralized sulfonated polymer or a sulfonated polymer capable of neutralised in situ such as herein described and having a sulfonate content of 4 to 200 meq. per 100 grams of said neutralized sulfonated polymer,

Compl. specn. 19 pages

Drgs. 1 sheet

Ind. Cl.: 40 H 80 K

172622

Int. Cl4: B01D 13/04.

A PROCESS FOR PREPARING A COMPOSITE MEMBRANES FOR ENHANCED FLUID SEPARATION AND THE MEMBRANES PREPARED BY SUCH PROCESS.

Applicant: UNION CARBIDE CORPORATION, MANUFACTURERS, A CORPORATION ORGANIZED AND EXISTING UNDER THE LAWS OF THE STATE OF NEW YORK, UNITED STATES OF AMERICA; WITH OFFICES AT: OLD RIDGEBURY ROAD, DANBURY, STATES OF CONNECTICUT, 06817, UNITED STATES OF AMERICA.

Inventors: SAMUEL CHEW WILLIAMS, BENJAMIN BIKSON, JOYCE KATZ NELSON, ROBERT DOUGLAS BURCHESKY.

Application for Patent No. 285/Del/88 filed on 7 April 1988.

Appropriate office for opposition proceeding (Rule 4, Patent Rule 1972), Patent Office Branch, New Delhi-5.

17 Claims

A process for preparing a composite membrane capable of selectively permeating a more readily permeable component of a fluid mixture in gas, pervaporation or perstruction separation operations and having a separation layer that determines the separation characteristics of the membrane and a porous support layer, the process comprising

- (a) coating the support layer with a separation layer of membrane material, said support layer containing a controlled amount of liquid in the range of from 10% to 90% by weight of the liquid present in said support layer in substantially wet form, said liquid being a solvent or non-solvent for the material of the separation layer; and
- (b) drying said separation layer on the support layer, the presence of said liquid in the support layer precluding any appreciable penetration of the membrane material into the pores of said support layer, the separation layer thereby being of a non-occlusive nature and potentially of an asymmetric nature, with a less dense region adjacent to the outer surface of the support layer and a more dense outer region

adjacent to the outer surface on said separation layer, whereby the composite membrane exhibits essentially the separation characteristics of the membrane layer while achieving an advantageous combination of selectivity and permeability for the desired separation of said fluid mixture.

Compl. Specn. 32 pages

Ind, Cl.: 32-B [IX (I)]

172623

Int. Cl.4: C07C, 5/22.

PROCESS FOR UPGRADING THE OCTANE NUMBER OF C_5 AND C_6 COMPONENTS OF A FEEDSTREAM CONTAINING C_5 , C_6 AND C_7 HYDROCARBONS.

Applicant: UOP INC., A CORPORATION ORGRANIZED UNDER THE LAWS OF THE STATE OF DELAWARE IN THE UNITED STATES OF AMERICA, WITH ITS PRINCIPAL OFFICE LOCATED AT 25 EAST ALGONQUIN ROAD(DES PLAINES, ILLINOIS, UNITED STATES OF AMERICA.

Inventor: FREDERICK MICHAEL HIBBS.

Application for Patent No. 312/Del/88 filed on 12 April 1988.

Appropriate Office for opposition proceedings (Rule 4, Patent Rule 1972), Patent Office Branch, New Delhi-5.

5 Claims

A process for upgrading the octance number of C_5 and C_6 components of a feedstream containing C_8 , C_6 and C_7 hydrocarbons, said process comprising:

- (a) passing said feedstream into a fractionation zone and separating said feedstrem therein into higher and lower boiling components;
- (b) withdrawing from a lower portion of said fractionation zone a reforming input stream comprising C₇ plus hydrocarbons and passing said reforming input stream to a reforming zone;
- (c) withdrawing a sidecut stream comprising normal hexane and lower boiling hydrocarbons from said fractionation zone and passing said sidecut stream to an isomerisation zone;
- (d) contacting said sidecut stream in said isomerisation zone with a Group VIII noble metal catalyst to produce an octane enhanced isomerisation zone effluent stream rich in C_5 and C_6 isoparafin and lower boiling hydrocarbons;
- (e) recycling at least a portion of said octane enhanced isomerisation zone effluent stream to said fractionation zone; and
- (f) withdrawing from said fractionation zone a high octane overhead product stream comprising C_5 and C_6 isoparafiln and lower boiling hydrocarbons.

Compl. Speen. 30 pages

Drgs. 1 Sheet

Ind. Cl.: 32E

172624

Int, Cl.: B29D 7/01, C0TJ 5/18.

A PROCESS FOR THE PRODUCTION OF ORIENTED POLYOLEFINE FILMS.

Applicant: EXXON CHEMICAL PATENTS INC, A CORPORATION ORGANISED AND EXISTING UNDER THE LAWS OF THE STATE OF DELAWARE, UNITED STATES OF AMERICA OF 1900 EAST LINDEN AVENUE, LINDEN, NEW JERSEY 07036, UNITED STATES OF AMERICA.

Inventor: BERNARD LOUIS LUC BOSSAERT.

Application for Patent No. 332/Del/88 filed on 19 April 1988.

Convention application filed on 21 April 1987/8709446/ U.K.

Appropriate office for opposition proceeding (Rule 4, Patent Rule 1972), Patent Office Branch, New Delhi-5.

5 Claims

A process for the production of oriented polyolefin films by blending and extruding polyolefin and a rosin or resin, preferably hydrogenated, characterised by first blending under high shear conditions, a polyolefine and a rosin or resin to form a concentrate containing from 50 to 80 wt% of resin or rosin and secondly additional polyolefin is blended under high shear conditions with the concentrate in a melt extrusion step to form a film containing a reduced proportion of resin or rosin of from 5 to 30 wt %, the blending shear in the first step being higher than in the second step.

Compl. Speen. 22 pages.

Ind. Cl.: 98 I

172625

Int. Cl.: F 24 J 2/10, B 32 B 17/06, C03C 17/40.

A TRANSPARENT SHEET HAVING A LOW REFLECTANCE COATING AND A METHOD OF MAKING A TRANSPARENT COATED SHEET.

Applicant: PPG INDUSTRIES, INC., A CORPORATION ORGANISED UNDER THE LAWS OF THE STATE OF PENNSYLVANIA, UNITED STATES OF AMERICA, OF ONE PPG PLACE, PITTSBURGH 22, STATE OF PENNSYLVANIA 15272, UNITED STATES OF AMERICA.

Inventor: FRANK HOWARD GILLERY.

Applicant for Patent No. 432/Del/1988 filed on 16 May 1988.

Appropriate office for opposition proceeding (Rule 4, Patents Rules, 1972 Patent Office Branch, New Delhi-110 005.

Claims 16

A transparent sheet for the reflectance of solar energy comprising:

- (a) a transparent substrate;
- (b) a transparent film of a metal alloy oxide at a thickness which exhibits color deposited on a surface of said substrate; and
- (c) a neutral low flectance transparent metal alloy film deposited on said metal oxide film said films in combination providing a coated article which low transmittance and low reflectance.

A method of making a transparent sheet as claimed in any one of the preceding claims, wherein said method comprises sputtering onto a surface of a sheet of transparent glass or similar material a first transparent coating of the metal alloy oxide which exhibits color; and sputtering over said metal alloy oxide film a low reflectance transparent metal alloy film.

(Compl. Sepon. 10 pages.)

Ind. Cl.: 127 E

172626.

Int. Cl.: H02K 7/10.

EPICYCLOIDAL GEARBOX WITHOUT BEARINGS FOR SUPPORTING THE SEPARATE FITTED OUTLET SHAFT.

Applicant: L B TRANSMISSIONI MECCANICHE S R L. OF VIA BAZZANE LIA, CALDERARA DI RENO, BOLOGNA, ITALY, AN ITALIAN COMPANY.

Inventor: PAOLO CHINNI.

Application for Patent No. 454/Del/88 filed on 23 May 1988.


-_---

Appropriate office for opposition proceeding (Rule 4, Patents Rules, 1972 Patent Office Branch, New Delhi-110 005.

5 Claims

Epicycloidal gearbox without bearings for supporting the separate fitted outlet shaft, the gearbox having an independently fitted variator assembly complete with oil and ready use and for direct coupling on a reducer with outjutting male shaft also separately mounted, the variator comprising a driving disk (1) in engagement with a packet of Belleville washers (2) having therebetween an assembly of satellite gears (3) rolling on outer rings (4 and 5), said satellite gears (6), characterised by said satellite holding disk (7), characterised by said satellite holding disk (7), characterised by said satellite holding disk (7) being provided with an outlet quill for releasably coupling with the shaft (9) of the reducer without the necessity to dismantle the entire gearbox said releasable coupling being a tang (8) on the shaft (9) whereby the satellite holding disk (7) is keyed to the shaft (9) of the reducer and is able to be quickly released therefrom. a positioning screw (12) being provided on the variator body to hold the satellite holding disk (7) to enable quick alignment thereof with the reducer shaft (9), a pivot (10) being provided on said variator for adjustment of speed through a control screw.

Fig. 1



(Compl. Specn 8 pages.

Drgn. 1 sheet.)

Ind. Cl. . 155 F₂.

172627.

Int. CI: D 06M 13/44.

PROCESS FOR A FLAME RETARDANT TREATMENT OF A SUBSTRATE.

Applicant: ALBRIGHT & WILSON LIMITED, A BRITISH COMPANY, OF 210-222 HAGLEY ROAD WEST, OLDBURY, WARLEY, WEST MIDLANDS, ENGLAND.

Inventor: GEOFFREY WILLIAM SMITH.

Application for Patent No. 493/Del/1988 filed on 3 June 1988.

Convention date 5-6-1987/8713224/U.K.

Appropriate office for opposition proceeding (Rule 4, Patents Rules, 1972 Patent Office Branch, New Delhi-110 005.

Claims 13

A process for the fiame-retardant treatment of a substrate comprising cellulosic fibres and fibres co-blendable therewith, and process consisting essentially of the following steps:

- (a) impregnating said substrate with an aqueous solution of
 - (i) a tetrakis (hydroxyorgano) phosphonium compound; or
 - (ii) a water-soluble condensate of (i) with an organic nitrogen-containing compound; or

(iii) a mixture of (i) with said organic nitrogencontaining compound;

to provide an impregnated substrate carrying from 5% to 20% (by weight of the original weight of said substrate) of said tetrakis (hydroxyorgano) phosphonium ion (hereinafter referred to as "THP ion");

- (b) drying said impregnated substrate;
- (c) treating said dried substrate (b) with ammonia to cure said tetrakis (hydroxyorgano) compound to give a cured substrate;
- (d) repeating steps (a), (b) and (c) above to give a twice-cured substrate.

(Compl. Specn. 17 pages.)

Ind. Cl.: 206 A

172628.

Int. Cl.: HO1Q 15/00, 15/18.

A PARABOLIC ANTENNA REFLECTOR.

Applicant: SPARBANKEN SYD, OF P.O. BOX 252 S-271 00 YSTAD SWEDEN, A SWEDISH BANK DULY ORGANISED UNDER THE LAWS OF SWEDEN.


Inventor: REGIS GUSTAFSSON.

Application for Patent No. 503/Del/88 filed on 7 June 1988.

Appropriate office for opposition proceeding (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

Claims 4

A parabolic antenna reflector (1) which comprises a laminate formed from two layers (2, 4) of electrically well-conducting metal and an intermediate layer of plastics material of essentially uniform thickness and of low electrical conductivity, characterised in that the thickness and dielectric constant of the plastic layer are such that, at the operational frequency of the antenna, said reflector (1) forms a decoupling or by-pass capacitor (6) with a low impedance to earth (7) to attendantly reduce undesirable radiation side lobes.



(Compl. Specn. 7 pages.

Drgn. 1 sheet.)

Ind. Cl.: 64

172629.

Int. Cl.4: HO1 H 15/06.

A DEVICE RENDERING CONTACTORS ELECTRICALLY AND MECHANICALLY INOPERATIVE.

Applicant: LA TELEMECANIQUE ELECTRIQUE, A FRENCH CORPORATION, OF 33 BIS, AVENUE DU MARECHAL JOFFRE, 92000 NANTERRE, FRANCE.

Inventor: BERNARD FOURNIER.

Application for Patent No. 539/Del/88 filed on 21 June 1988.


Appropriate office for opposition proceeding (Rule 4, Patonts Rules, 1972) Patent Office Branch, New Delhi-110 005.

Claims 8

A device rendering contactors electrically and mechanically inoperative, said device comprising:

- a case (1) having two opposite parallel front walls, spaced apart from each other and, at least two opposite sidewalls which extend in planes substantially perpendicular to said front walls, said case (1) being mountable between two contactors disposed side by side;
- substantially coaxial apertures (14, 14a) located in the central region of said two front walls,
- first and second movement take-off means (6, 7) for respectively coupling with the mobile assembly of said two contactors through said substantially coaxial apertures (14, 14a) each of said movement take-off means (6, 7) being movable between two positions corresponding respectively to the work position and the rest position of the contactor with which it is associated;
- mobile members (2, 3) connected to and driven by said movement take-off means (14, 14a) for providing reciprocal inoperativeness, said mobile members (2, 3) having a travel distance such that the passage of one of the movement take-off (14, 14a) to the work position brings the element which corresponds with it to a position blocking the passage of the other movement take-off to the work position; and
- at least one input connection member (19, 21) mounted on one (40) of said sidewalls of said case, at least one output connection member (20, 22) mounted on the other said sidewall (39) casing.
- -- two switch devices (I, I_2) each comprising at least one pair of fixed contacts (15, 16-17, 18) connected respectively by connecting conductors to said at least one input connection member (19, 21) and said at least one output connection member (20, 22), and a mobile contact member (12) actuated by a corresponding mobile member providing inoperativeness.
- said switch devices (I₁, I₂), along with their corresponding said input and output connection members (19, 21, 20, 22) as well as with the corresponding connection conductors (12, 13) forming first and second through current lines, without crossing inside of the case (1) and directed transversely with respect to said sidewalls of the case (1).

FIG 1



(Compl. Specn. 14 pages.

Drgn. 4 sheets.)

Ind. Cl.: 14 Ag

172630.

Int. Cl.4: H01M 4/04, 8/00, 8/22.

AIR CATHODES.

Applicant: ALCAN INTERNATIONAL LIMITED, OF 1188 SHERBROOKE STREET, WEST, MONTREAL, QUEBEC, CANADA H3A 3G2, A COMPANY ORGANISED UNDER THE LAWS OF CANADA.

Inventor: WILLIAM HENRY HOGE,

Application for Patent No. 568/Del/1988 filed on 5 July 1988.

Appropriate office for opposition proceeding (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

Claims 8

An air cathode comprising a sheetlike laminate (16) formed of layers comprising first (34) and second (38) layers having opposed major surfaces (17, 18) respectively exposed for contact with a liquid electrolyte such as herein described and with air, said layers also having facing major surfaces, with said first layer (34) comprising a nonwoven fibrous web such as herein described impregnated with a mixture of carbon particles and an adhesive polymer such as herein described for holding the carbon particles in the web and said second layer (38) being permeable to air but not to said liquid electrolyte; and current-collecting means (36) in contact with said first layer (34) and connectable to external electrical circuitry; said facing major surfaces of said first and second layers (34, 38) being bonded together by heat seal polymeric bonding material (40) applied on said facing major surfaces in a pattern to provide an array or network of areas free of said bonding material extending substantially uniformly over said facing major surfaces.

(Compl. Specn, 27 pages.

Drgn, 1 sheet.)

Ind. Cl.: 164D [XXVII(3)], 152 E [XII(2)] 172631. Int. Cl.4: E01C 5/20.

A COMPOSITION FOR USE AS SUBSTITUTE SOIL MATERIAL.

Applicant: EN-TOUT-CAS PLC., A BRITISH COMPANY, OF SYSTON, LEICESTER, ENGLAND.

Inventors: PAUL HAWKINS AND JOHN DAVID DACHTLER.

Application for Patent No. 1125/Del/86 filed on 22nd December, 1986.

Appropriate office for opposition proceeding (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

Claims 10

A composition for use as substitute soil material consisting of a mixture of particulars or granular mineral material comprising sand, a synthetic polymeric material of the kind such as herein described and an organic material of the kind such as herein described having a viscosity such that it is substantially non-fluid at ambient temperatures so as to produce an inert, discrete material permanently capable of being raked when laid in a layer upon a substrate, the amount of said polymeric material and said organic material together being from 3.8 to 6.5 parts per 100 parts of said particulate or granular material and the amount of polymeric material being from 10 to 20 parts per 80 to 90 parts of said organic material.

(Compl. Speen. 9 pages.)

Ind. Cl.: 40 B.

172632.

Int. Cl.4: B01J 23/50.

A PROCESS FOR PREPARING CATALYSTS SUITABLE FOR OXIDIZING ETHYLENE WITH MOLECULAR OXYGEN TO ETHYLENE OXIDE.

Applicant: SCIENTIFIC DESIGN COMPANY, INC., A CORPORATION ORGANISED UNDER THE LAWS OF THE STATE OF DELAWARE, UNITED STATES OF AMERICA, OF 49 INDUSTRIAL AVENUE, LITTLE FERRY, NEW JERSEY 07643-1901. U.S.A.

Inventors: MITCHELL BECKER & KINDTOKEN LIU.

Application for Putent No. 155/Del/87 filed on 23 February 1987.

Appropriate office for opposition proceeding (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

Claims 13

A process for preparing catalyst suitable for oxidizing ethylene with molecular oxygen to ethylene oxide which comprises the production of a solution of a silver salt of a neo-acid having 7 or more carbon atoms followed impregnation of a porous support such as herein described with said solution and activation of the impregnated support by heating for a predetermined period of time to produce the desired catalyst, characterised by the single step of reactively mixing at least a stoichiometric amount of a silver compound with a unit amount of said neo-acid in the presence of a solvent such as herein described which is other than water at the boiling temperature of said mixture and under a pressure in the range of 0.01 to 0.08 bar until at least 90% of said neo-acid reacts with said silver compound to produce said solution of silver salt of neo-acid.

(Compl. Speen. 21 pages.)

Ind. Cl.: 140 A₂ X 1(2).

172633.

Int. Cl.4: B01F 17/28.

A PROCESS FOR MAKING A CARBOXYLIC SALT SUITABLE FOR THE PREPARATION OF A WATER-BASED FUNCTIONAL FLUID COMPOSITION.

Applicant: THE LUBRIZOL CORPORATION, A CORPORATION ORGANISED UNDER THE LAWS OF THE STATE OF OHIO, UNITED STATES OF AMERICA, OF 29400 LAKELAND BOULEVARD, WICKLIFFE, OHIO 44092 UNITED STATES OF AMERICA.

Inventor: JOHN WESLEY FORSBERG.

Application for Patent No. 481/Del/87 filed on 4 June 1987.

Appropriate office for opposition proceeding (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

Claims 20

A process for making a carboxylic salt suitable for the preparation of a water-based functional fluid composition, said process comprising the step of reacting component (a) with component (b) under conventional salt-forming conditions to form the required salt, wherein said component (a) comprising at least one hydrocarbyl substituted carboxylic acid or anhydride, the hydrocarbyl substitutent of said acid or anhydride having an average of from 12 to 500 carbon atoms, and said component (b) comprising at least one amine, alkali or alkaline earth metal, or alkali or alkaline earth metal compound; with the provisio that:

said component (b) is other than an N-(hydroxyl-substituted hydrocarbyl) amine and/or hydroxyl-substituted poly (hydrocarbyloxy) analog of said N-(hydroxyl-substituted hydrocarbyl amine,

(Compl. Speen. 73 pages

Drgs. 2 sheets)

Ind. Cl.: 117 C LXIV (5).

172634

Int. Cl.: E 05 B 27/00, 27/08.

CYLINDER LOCK.

Applicant: WIDEN INNOVATION AB, A SWEDISH COMPANY, OF P.O. BOX 37, \$-644.00 TORSHALLA. SWEDEN.

Inventor: BO WIDEN,

Application for Patent No. 600/Del/87 filed on 15-7-87.


Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

13 Claims

A cylinder lock (18) comprising : a cylinder shell (19);

- a key plug (20) rotationally mounted in said cylinder shell (19) to provide a line of close contact (21) between said cylinder shell and said key plug;
- a key slot (11) extending into said key plug (20) parallel to a rotational axis of said key plug for receiving a key blade (1); at least one locking tumbler (23a-23e) having an elongated body portion (23ab-23eb) guided in a transverse cavity (33a-33e) which corresponds to said elongated body portion (23ab-23eb) and provided in said key plug (20), said elongated body portion rotationally moveable about its longitudinal axis (B); and a fence member or side bar (29) located so as to block said locking tumbler (23a-23e) and be displaced by rotational positioning (23a-23e) and be displaced by rotational positioning of said locking tumbler by a properly shaped key blade, said fence member in said displaced position clearing the line of close contact between said cylinder shell and said key plug;

characterized in that said at least one locking tumbler (23a-23e) is further provided with a finger (23af-23ef), which projects transversely outwardly from said longitudinal axis of said elongated body portion (23ab-23eb), said elongated body portion being cylindrical and guided in a bore (33a-33e) corresponding to said cylindrical body portion, said finger (23af-23ef) projecting into said key slot (11) to enable engagement with said key blade (1) and consequent rotational positioning of the finger and elongated body position of the locking tumbler about said axis (B) inserting said key. inserting said key.



(Compl. Speen, 21 pages

Drgs. 4 sheets)

Ind, Cl.: 84 C₁.

172635

Int. Ch. : C 10 B 3/02. COKING APPARATUS.

Applicant: BERGWERKSVERBAND GmbH., A GERMAN COMPANY, OF FRANZ-FISCHER-WEB 61, 4300 ESSEN 13, WEST GERMANY.

2-307 GI/93

Inventors: GERD NASHAN, KLAUS WESSIEPE, HERIBERT BERTLING, WOLFGANG ROHDE, MANFRED BLASE, MANFRED GALOW, URICH KOCHANSKI, HEINZ DURSELEN, JOHANNES JANICKA, DIETER STALHERM, JAOCHIM HOITZ, JURGEN TIETZE AND RALF SCHUMACHER.

Application for Patent No. 1086/Del/87 filed on 16th Dec. 1987.

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

5 Claims

Coking apparatus functioning on the batch-wise feeding of coking blends, preferably on a hardcoal base to a reactor which is heated indirectly by heat recovery in regenerators or recuperators, comprising :

high-capacity reactors (100) united to form a reactor block, each said reactor computing a reactor chambere (1) and two rigid lateral walls (2), flue walls (3) disposed within and delimiting the said reactor chamber, said flue walls having a planeparallel configuration, rigidly supported by the said lateral walls and comprising an array of vertical flues (4a, 4b) with separate control and/or adjusting elements (19) therefore, and regenerators or recuperators (R) for indirect heating by heat recovery, said lateral walls (2) of the reactors are interconnected and said regenerators or recuperators are located beneath the flue walls (3) and/or the reactor chambers.

(Comp. Specn. 17 pages,

Drgs. 8 sheets)

Ind. Cl.: 32 B.

172636

Int. Cl.4 : C 10 G 9/28.

PROCESS OF THERMALLY CRACKING HYDRO-CARBONS USING PARTICULATE SOLIDS AS HEAT CARRIER.

Applicant: EXXON RESEARCH AND ENGINEERING COMPANY, A CORPORATION ORGANISED AND EXISTING UNDER THE LAWS OF THE STATE OF DELAWARE UNITED STATES OF AMERICA, OF P.O. BOX 390, FLORHAM PARK, NEW JERSEY 07932, UNITED STATES OF AMERICA.

Inventors: JOHN BOTELER YOURTEE & JOHN MORRIS MATSEN.

Application for Patent No. 1135/Del/87 filed on 28th Dec., 1987.

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

7 Claims

A process for thermally cracking hydrocarbon such as herein described to produce lighter products such as ethylene whereing a hydrocarbon feed gas which may contain some liquid is contacted with hot particulate solids of the kind such as herein described in a reactor, said process comprising distroducing said particulate solids at low velocity as herein described into contact with the feed gas at substantially higher velocity to entrain the solids in the gas and thereby higher velocity to entrain the solids in the gas and thereby transfering the heat from solids to feed and crack the same, allowing the solids to accelerate in passing through the reactor and terminating the reaction in a manner such as herein described substantially before the solids attain the velocity of the product gas in order to separate said solids from the gases products and quenching the gases products in a manner such as herein described.

(Compl. Speen. 41 pages

Drg. 1 sheet)

Ind. Cl.: 206 E. [LXII].

172637

Int. Cl. : G 06 F 7/00, 15/00.

COMPUTER SYSTEM.

Applicant(s): INTERNATIONAL BUSINESS MACHINES CORPORATION, A COMPANY ORGANISED AND EXISTING UNDER THE LAWS OF THE STATE OF NEW YORK, UNITED STATES OF AMERICA, OF ARMONK, NEW YORK 10504, UNITED STATES OF AMERICA.

Inventors: IAN ANTHONY CONCILIO, CHESTAR ASBURY, IEFFREY ALAN HAWTHORNE, GEORGE EDUARDO LENTA AND LONG DUY NGUVEN.

Application for Patent No. 179. Del 88 filed on 09 Mar 1988.


Convention Date 10-12-1987/8728921/U.K.

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

6 Claims

A computer system comprising a central processor unit, a direct memory access controller, a system bus for coupling said central processor unit and said direct memory access controller, a central arbitration control circuit, and a family bus for coupling a plurality of peripheral devices to said direct memory access controller, to said system bus, and to said central arbitration control circuit, characterised in that first peripheral devices each of which has an internal arbitration circuit are coupled to said central arbitration control circuit for determining access by source of the first peripheral devices to a single direct memory access channel in accordance with arbitration data from said internal arbitration circuits, and that second peripheral devices which have no internal arbitration circuits are coupled to a soft request arbitration unit which receives arbitration data related to the second peripheral devices from the central processor unit for determining access by the source of the second peripheral devices to a second single direct memory access channel,

Fig. 1



(Compl. Specn. 15 pages.

Drgs 7 sheets)

Ind. Cl.: 143 D₁

172638

Int. Cl.4: H 05 K 5/02,

A CONTAINER FOR LOOSELY HOUSING ONE OR A SERIES OF ELECTRICAL COMPONENTS.

Applicant: YEN WEI HSIUNG. A TAIWANESE CITI-GEN OF 8 CHIA PING ROAD, JURONG TOWN. # 01-01 TO # 01-08, SINGAPORE 2261.

Inventor: YEN WEI HSIUNG.


Application for Patent No. 447/Del/1988 filed on 20-05-1988.

Convention date 26-05-1987/8712338/U.K.

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005.

7 Claims

A container for loosely housing one or a series of electrical components having a row of terminal pins protruding in substantially the same direction from a single side of the component body, said container comprising an elongate tubular member having a first hollow component body receiving compartment and a second hollow terminal pin receiving compartment, said first and second compartments of said tubular member having conductive portions which are contacted by said electrical component where housed in said tubular by said component, said conductive portions being electrically interconnected.



(Compl. Speen, 13 pages

Drgs. 07 shee(s)

Ind. Cl.: 101 B.

172639.

Int. Cl.': E 02 B 3/00.

APPARATUS FOR THE COMBATTING MARINE GROWTH ON OFFSHORE MARINE STRUCTURES.

Applicant (s): IEV INTERNATIONAL PTY. LIMITED, A COMPANY INCORPORATED UNDER THE LAWS OF THE STATE OF NEW SOUTH WALES, OF 8TH FLOOR, 35 SPRING STREET, BONDI JUNCTION, NEW SOUTH WALES 2022, AUSTRALIA.

Inventor: CHRISTOPHER NGHIA DO.


Application for Patent No. 461/Del/88 filed on 24 May 1988

Appropriate office for opposition proceedings (Rule 4, Patent Rules, 1972) Patent Office Branch, New Delhi-110005.

10 Claims

Apparatus for combating marine growth on offshore marine structures, said apparatus (1) surrounding a submerged structural support member of a said offshore marine structure for scraping marine growth therefrom and for preventing marine growth from establishing or re-establishing thereon, said apparatus being powered by the utilisation of ocean forces in the form of waves, swells, tides and currents, said apparatus comprising a plurality of flexible marine growth combating collars (2.3) connected together in spaced-apart array

by means of linking members (4) disposed substantially parallel to a said structural support member to thereby remove fouling marine growth threfrom, or prevent growth or -regrowth of fouling marine organisms thereon.



(Compl. Specn. 15 pages

Drgs. 6 Sheets)

Ind. Cl.: 39L (III).

172640

Int. Cl4. : Colg 3/02.

PROCESS FOR PRODUCING SUPERCONDUCTING OXIDE MATERIAL.

Applicant: INSTITUTE TSRUKTURNOI MAKROKINE-TIKI AKADEMII NAUK USSR. OF P/O CHERNOGO-LOVKA, MOASKOVSKAYA, OBLAST. USSR.

Inventors: ALEXANDR GRIGORIEVICH MERZHA-NOV, INNA PETROVNA BOROVINSKAYA, MIKAEL DAVIDOVICH NERSESIAN, ANDREI GENNADIEVICH PERESADA.

Application for Patent No. 466/Del/88 filed 25 May 1988.

Appropriate office for opposition proceedings (Rule 4. Patent Rules, 1972) Patent Office Branch, New Delhi-110005.

18 Claims

A process for producing a superconducting oxide material which comprises mixing in their stoichiometric ratio a non-combustible ingredient with a combustible ingredient to produce an exothermal mixture, said non-combustible ingredient being selected from the group consisting of one or more of an oxide, halide, nitrate, carbonate, oxalate of a rare-earth metal of the periodic system selected from scandium, yttrium, lanthanides or mixtures thereof; or an oxide, peroxide, carbonate, nitrate, halide of a metal of Group I of the periodic system; or an oxide, peroxide, nitrate or helide of a metal of group II of the periodic system.

said combustible ingredient being one or more metal selected from the group consisting of;

said rare-earth metal of the periodic system; a metal of Group I of the periodic system; a metal of group II of the periodic system; and/or bydride of at least one metal selected from the said rare-earth metal of the periodic system; and

a metal of Group II of the periodic system, subjecting said exothermal mixture to combustion by igniting it in the presence of an oxygen-containing medium with an excess of an oxidizing agent of the kind such as hereinbefore described and maintaining the excess of the oxidizing agent till completion of the reaction to produce said superconducting oxide material.

(Cmopl. Speen. 27 Pages)

Ind. Cl.: 40 F [1V(1)]

172641

Int. Cl. : B 01 D, 3/40.

"PROCESS FOR SEPARATING ETHYLENE OXIDE FROM IMPURE ETHYLENE OXIDE CONTAINING FORMALDEHYDE AND/OR ECETALDEHYDE AS IMPURITIES, AND WATER".

Applicant: A FOCHEM A FRENCH BODY CARPORA-TE OF LA DEFENSE 10 4 & 8 COURS MICHELET 92800 PUTEAUX FRANCE.


Inventors: 1. FRANCIS DELANNOY, 2. GERARD LETRAY.

Application No. 900/Mas/88 filed on 20th December 1988.

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, Madras.

9 Claims

Process for separating ethylene oxide from impure ethylene oxide containing at least 80% ethylene oxide, with formaldehyde and/or acetaldehyde as impurities and water, by distillation in a column with reflux wherein the aid distillation is carried out under such conditions that in he liquid stream which leaves the bottom of the column the weight ratio of ethylene oxide to that of water is from 0.15: 1 to 3:1 while the ethylene oxide resulting from the separation from formaldehyde and from acetaldehyde leaves at the top of the column; the column operating at an average absolute pressure of 2.5 to 5 bars and the temperature at the bottom of the column is from 40°C to 60°C.



(Compl. Speen. 21 pages;

Drg. 1 sheet)

Ind. Cl. 187 H [LXI(2)]

172642

Int. Cl.4: H 04 M 1/78.

A TRANSMISSION SYSTEM FOR PICTURE PHONE.

Applicants: KABUSHIKI KAISHA MYKOMU, OF KITA-4JO-NISHI 4-CHOME, CHUO-KU, SAPPORO-SHI, HOKKAIDO, JAPAN, A JOINT-STOCK COMPANY.


Inventor: KIYJOSHI KURODA.

Application No. 886/Mas/88 filed on 14th December, 1988.

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, Madras.

6 Claims

A transmission system for picture phone comprising at least two terminal devices interconnected via one or more transmission lines through croses talk cancelling circuits provided with each said terminal devices, a frequency division system for multiplying at least one of the signals from sound signal and image data signal for transmitting image transmission signal and voice transmission signal simultaneously and bi-directionally using a single side band system with enhanced transmission speed and tone quality.



(Compl. Specn. 23 pages

Drgs. 11 sheets)

Ind. Cl.: 127 I [LXV(1)]

172643

Int. Cl.4: B 62 D 55/08.

A PIVOT ASSEMBLY.

Applicants: CATERPILLAR INC., OF 100 N E ADAMS STREET, PEORIA, ILLINOIS 61629-6490, U.S.A. A CORPORATION DULY ORGANISED AND INCORPORATED UNDER THE LAWS OF THE STATE OF DELAWARE, U.S.A.

Inventors: DRYAN GERARD LAMMERS CHARLES FREDERICK SIECK.


Application No. 4/Mas/89 filed on 3rd January, 1989.

Convention dated 3rd January, 1988; No. 573,743 (Canada):

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, Madras.

9 Claims

A pivot assembly comprising: a shaft member having a mounting portion, a frustoconical bearing receiving surface, and an end cap receiving portion; a frame member having a through bore, and first and second bearing receiving surfaces shaped complimentary to said frustoconical surface said bore, said bore being adapted to receive said shaft member; an end cap having a cavity and a bearing receiving surface, said cavity adapted to receive said end cap receiving portion; two elastomeric bearings, one of the said elastomeric bearing positioned between said bearing receiving surface of said shaft member and said first bearing receiving surface of said frame member, and the another said elastomeric bearing positioned between said bearing receiving surface of said end cap and said second bearing receiving surface of said frame member; and means for securing said end cap to said end cap receiving portion of said shaft member, and for securing said frame to said shaft member, said elastomeric bearings being compressed when said frame and shaft members are secured together.



(Compl. specn. 13 pages

Drgs. 2 sheets)

Ind. Cl.: 98 H [VII (2)]

172644

Int. Cl.4: H 01 L-35/04.

"A THERMOCAUPLE".

Applicant: TEMPRA THERM (PTY) LIMITED A SOUTH AFRICAN COMPANY OF 24 RUDOLPH STREET SUNDERLAND RIDGE VERWOERDBURG SOUTH AFRICA.

Inventor: ADRIAN LIONEL GRAY.


Application No. 97/Mas/89 filed on 6th February 1989.

Appropriate office for opposition proceedings (Rule 4. Patents Rules, 1972) Patent Office Branch, Madras.

10 Claims

A thhermocouple (1) comprising a bimetal junction (18) located in a closed outer end of a length of quartz glass tube (21) with the separated free ends of junction wires (19,20) connected to the compensating conductors (9,17) of the thermocouple, characterized in that said compensating conductors (9,17) are connected to a plug (8) of thermoplastic synthetic plastics material inserted into the open opposite end

of the tube (21), and that the said separated free ends of said junction wires (19,20) project from said open opposite end of the tube (21) around said plug (8) and are firmly embedded in and/or held in contact with the latter.



(Comp. specn. 15 pages

Drgs. 2 sheets)

Ind. Cl.: 85 J, 105 C [XXXI], [XLI(7)]

172645

Int. Cl.4: F 27 D 23/00; G 05 B 19/00

AN APPARATUS FOR THE POSITIONING OF METAL SLABS INTO A FURNACE.

Applicants: ITALIMPIANTI SOCIETA ITALIANA IM-PIANTI P. A. OF PIAZZA PICCAPIETRA 9, I-16121 GE-NOVA, ITALY, ITALIAN COMPANY.

Inventors: BRUNO MEINI, ALLESSANDRO FABBRINI GLOVANNI SCARSI.


Application No. 209/Mas/89 filed on 17th March 1989.


Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, Madras.

5 Claims

An appratus for the positioning of metal siabs (2) into a furnace comprising a roller-path (1) or the like for feeding the slabs (2) to the furnace-mouth (3), said roller-path being arranged normally to the direction of entrance and advance into the furnace, and with a plurality of sources of light (5) directed towards said slabs in the region opposite the furnace-mouth (3), as well as with telecameras (9) directed towards the region opposite the furnace-mouth (3) and connected to display monitors (10), and with a microprocessor (11) connected to the monitors (10), wherein at least two sources of light (5) arranged on the side of the roller-path (1) away from the furnace-mouth (3) and each projecting at least two blades of light (6, 7, 8) on said slab which are normal to the direction of entrance and advance into the furnace, into an associated lateral region of the furnace-mouth(3), and at least

two telecamoras (9) directed towards the roller-path (1) and arranged above the furnace-mouth (3), each of which is associated with one of the sides of said furnace-mouth (3) and is connected to a display monitor (10), while said microprocessor (11) is connected both to the monitors (10) and to a programmable-logic electronic control unit 12, for generating control signals for the roller-path (1).





(Compl. Specn. 16 pages

Drgs. 4 sheets)

Ind. Cl.: 195 B, D [XXIX(3)] & 107 G [XLVI(2)], 172646

Int. Cl. : F 16 K 7/00

A DUEL-FUEL PRESSURE REGULATOR FOR THE FEED SYSTEM OF AN INTERNAL COMBUSTION ENGINE.

Applicant & Inventor: EDOUARD TOUILLET OF SAU-TONNE MARTAIZE 86330 Saint-Jean-de-Sauves, France, a French citizen.

Application No. 250/Mas/89 filed on 29th March, 1989,

Appropriate office for the opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office, Madras Branch.

11 Claims

A dual-fuel pressure regulator comprising: first and second main chambers separated by a deformable first wall portion;

first and second secondary chambers each sharing a common second wall portion with a respective one of said first

outside said wall portion main chambers constituted by said deformable first wall portion;

two valves defined in respective ones of said second wall portions, with each valve being constituted by a seat and a valve member suitable for co-operating with said

first coupling means coupling said two valve members to each other and to said deformable first wall portion;

feed means for feeding the two fluids into respective ones of the two secondary chambers;

outlet duct means from said two main chambers for each of the two fluids respectively;

wherein the first and second secondary chambers include respective deformable third and fourth wall portions situated outside second wall portions said deformable third and fourth wall portions being equal in area, and that it also includes second coupling means coupling said deformable third and fourth wall portions to said first coupling means, and means for applying the pressure of the fluid contained in the first and second main chambers to said deformable third and fourth wall portions, respectively.


Applicant: FRAMATOME A FRENCH COMPANY OF TOUR FIAT L PLACE DE LA COUPOLE-92400 COUR-BEVOIE FRANCE. Inventor: FRIZOT ALAIN.

Application No. 311/Mas/89 filed on 25th April 1989.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972), Patent Office Branch, Madras.

8 Claims

A device for screwing and unscrewing a nut (30-32) on a coupling member (2), characterized by a framework (14) pivoting around a shaft (15) parallel to the coupling member (2) and supporting means (17, 19, 22, 26) for driving in rotation the nut (30-32) to be screwed or unscrewed and means (20, 24) for moving the said means for driving in rotation along an axis parallel to the axis of the coupling member (2), and at a speed identical with that of the nut in motion while it is being screwed or unscrewed.



(Compl. Speen, 17 pages


Drgs. 2 sheets)

172647

Int. Cl. : B 23 p 19/06.

Ind Class: 129 K [XXXV].

"A DEVICE FOR SCREWING AND UNSCREWING A NUT ON A COUPLING MEMBER".



(Compl. Specn. 13 pages

Drgs. 4 sheets)

Ind. Cl.: 195 C [XXIX(3)].

172648

Int. Cl.*: F 16 K 1/12.

SHUTOFF AND REGULATING VALVE.

Applicant: XOMOX INTERNATIONAL GmbH & CO., A GERMAN COMPANY, OF VON-BEHRING-STR. 15, D-8990 LINDAU, FEDERAL REPUBLIC OF GERMANY.


Inventor: WOLFGANG GONSIOR.

Application No. 543/May/89 filed on 19th July 1989.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972), Patent Office Branch, Madras.

16 Claims

A shutoff and regulating valve comprising a rotatable stem; a shutoff element in the form of a stopcock mounted on said stem to rotate therewith; a housing in which said shutoff element is arranged; a housing cover through which said stem extends; a first sealing element for scaling said stem where it extends through said housing cover; a second scaling element arranged on the surface of said cover, and an annular disk for supporting said first sealing element on the underside of said cover. said cover.



(Compl. Specn. 17 pages

Drgs. 2 sheets)

Ind. Cl.: 39 O [III]

172549 Int. Cl.4: C 0B 33/20.

A PROCESS FOR THE HYDROTHERMAL PRODUCTION OF SODIUM SILICATE SOLUTIONS.

Applicants: HENKEL KOMMANDITGESELLSCHAFT AUF AKTIEN, A COMPANY ORGANIZED AND EXISTING UNDER THE LAWS OF THE FEDERAL REPUBLIC OF GERMANY, OF HENKELSTRASSE 67, 4000 DUSSEL-DORF, GERMANY

Inventors: RUDOLF NOVOTNY, ALFRED HOFF, XOST SCHURTZ.

Application No. 850/Mas/89 filed on 22nd November,

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972), Patent Office Branch, Madras.

10 Claims

A process for the hydrothermal production of sodium silicate solutions having high SiO2 : Na2O molar ratios by reaction of quartz sand with aqueous sodium hydroxide solutions in a pressure reactor at temperatures in the range from 150 to 300°C and under saturated steam pressures corresponding to those temperatures, characterized in that the sodium silicate solutions obtained, which have SiO., : Na2O molar ratios of less than 2.9: 1, are subsequently reacted with a quartz conditioned at temperatures above 100°C to the melting point. at temperatures in the range from 150 to 300°C and under saturated steam pressures corresponding to those temperatures

Drg Nil)

Ind. Cl.: 136-E-[GROUP-XIII]

172650

Int. Cl.4: B 29 C 67/20.

A THREE-DIMENSIONAL CELLULAR WALL

Applicant & Inventor: TROTIGNON JEAN-PIERRE OF 13 LA ROSERAIE, 114 AVENUE DE PARIS, 78000 VERSAILLES, FRANCE, A FRENCH NATIONAL.

Application No. 33/Mas/91 filed January 21, 1991.

Divisional to Patent Application No. 261/Mas/87; Ante dated to April 7, 1987.

Appropriate Office for Opposition Proceedings (Rule 4, Patents Rules, 1972), Patent Office Branch, Madras.

5 Claims

A three-dimensional cellular wall produced by extruding a semisoft substance such as herein described through a die a semisor substance such as never described through a die and allowing it to harden beyond the die, wherein each cell (31) is delimited by by a plurality of partitions (31a to 31f) extending substantially transversely to the thickness of the wall, wherein each cell has at least four partitions (31c 31d, 31e and 31f) slope both relative to a direction normal to the faces of the wall and relative to the extrusion direction in a function paramidal change. in a frusto pyramidal shape.

(Compl. Specn, 22 pages

Drgs. 4 sheets)

172651

Int. Cl. 131 A2.

Int. Cl.4 GOIM 3/00.

A DEVICE FOR TESTING THE BOTTOM AND TOP HOLE CEMENTING PLUG FOR USE IN OIL WELLS.

Applicant: OIL & NATURAL GAS COMMISSION, TEI BHAVAN, KAUAGARH ROAD, DEHRA DUN-248195, INDIA, A SOCIETY REGISTERED UNDER THE SOCIETIES REGISTRATION ACT.


Inventor: SURESH KUMAR BATRA.

Application for Patent No.: 363/DEL/88 filed on 27-4-1988.

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005

(Claims 7)

A device for testing of top and bottom hole connecting plugs for use in oil wells comprising a frame (1) having a base plate (3) and a top plate (4) secured with each other by means of pillers (2), a cylinder (6) mounted on said base plate (3) for accomodating said plug (9) therein, a removable cover plate (7) to close said cylinder (6) being provided such as to be pressed by means of rotatable wheel (14) provided above said top plate (4), means being provided with said cover plate (7) for introducing a test fluid under pressure within said cylinder (6) and detection means under pressure within said cylinder (6) and detection means provided with said plug (9) for detecting a leakage of suid through said plug.



(Complete Specification 8 pages drawing one sheet).

Ind. Cl. 206E

172652

Int. Cl.4: H03F 3/00.

LINEARIZED DIFFERENTIAL AMPLIFIER.

Applicant(s): MOTOROLA, INC., A CORPORATION OF THE STATE OF DELAWARE, UNITED STATES OF AMERICA. OF 1303 EAST ALOGONGUIN ROAD, SCHAUMBURY, ILLINOIS 60196, UNITED STATES OF AMERICA.

Inventor(s): LAWRENCE MARVIN ECKLUND and CHARLES JAMES MARIK.

Application for Patent No. 366/Del/88 filed on 27 Apr 1988.

Appropriate office for opposition proceedings (Rule 4, Paten's Rules, 1972) Patent Office Branch, New Delhi-110 005

(Claims 7)

A linearized differential amplifier (10) comprising a differential amplifier (11, 12).

input (19) means connected to the differential amplifier for providing an input signal;

reference (2, 3) means connected to the differential amplifier for providing a reference signal;

output means connected (102) to the differential amplifier for providing an output signal substantially related to a difference between said input signal and said reference signal;

first feedback means (21, 24) coupled between;


said differential amplifier and said input means; and said differential amplifier and said reference means;

for substantially linearizing said output signal with respect to said input signal within a first operating range; and second feedback means coupled between;

said differential amplifier and said input means; and

said differential amplifier and said reference means;

for restricting said first operatin grange to a second operating range that is at least slightly smaller than said first operating range.



(Complete specification 11 pages drawing sheets 2)

Ind. Cl: 40B

172653

Int. Cl.4: B01J 29/18.

PROCESS FOR THE PREPARATION OF HIGH SILICA, LARGE PORT MORDENITES.

Applicant(s): COUNCIL OF SCIENTIFIC AND IN-DUSTRIAL RESEARCH, RAFI MARG, NEW DELHI-110001, INDIAN. AN INDIAN REGISTERED BODY INCORPORATED UNDER THE REGISTRATION OF SOCIETIES ACT (ACT XXI OF 1860).

Invenior(s): ASHA JEEVAN CHANDWADKAR AND PAUL RATNASAMY.

Application for Patent No. 367/Del/88 filed on 27 Apr 1988.

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005

(Claims 7)

A process for the preparation of a high silica, large port mordenites the said mordenite being characterised by the X-ray diffraction pattern of the kind such as herein described and being represented in terms of mole ratios of oxides by the formula $R_2O:M_2O:Al_2O_3:(15-60)\:\mathrm{SiO}_2:ZH_2O$ wherein R is tetraethyl ammonium, M is an alkali metal and Z is between 7-10 which comprises forming a reaction mixture by mixing water, tetraethyl ammonium bromide, a source of alkali such as sodium hydroxide, a source of alumina such as herein described and an assure of silica such as herein described and maintaining the said reaction mixture at a temperature of between 100 and $200^{\circ}\mathrm{C}$ for a period of 10-100 hrs. to provide the said mordenite, separating the mordenite washing drying and cleaning the mordenite at a temperature in the range of $400^{\circ}\mathrm{C}$.

(Complete specification 18 pages).

Ind. Cl.: 168C

172654

Int. Cl.4: E01F 13/00.

ANTI-INTRUSION BARRIER FOR STOPPING AN UNAUTHORIZED LAND VEHICLE FROM CROSSING-OVER TO A GIVEN ZONE.

Applicant: GERARD MATHE, A FRENCH CITIZEN OF 146, RUE STEHELIN, F-BORDEAUX, FRANCE.


Inventor: GERARD MOTHE.

Application for Patent No. 385/Del/1988 filed on 3-5-1988.

Appropriate office for opposition proceedings (Rule 4, Paten's Rules, 1972) Patent Office Branch, New Delhi-110 005

(Claims 5)

An anti-intrusion barrier for stopping an unauthorized land vehicle from crossing over to a given zone said barrier comprising a rectangular, shaped self-supporting frame (1) having a stop-barrier (2) connecting at one end of said frame (1) and an access-control barrier (13) up stream of said stop-barrier (2), said control barrier (13) being connected to the other end of said frame (1), a mechanical release linkage (9, 11, 17, 18) located between said barriers to connect said stop barrier and said access control barrier.



(Complete specification 08 pages) (drawing 01 sheet),

Ind. Cl.: 179D.

172655

Int. Cl.': F16J 15/16.

Title: A SEALING LINER FOR A CLOSURE MEANS.

Applicant: APPLICATIONS MECANIQUES ET ROB-INETTERIE INDUSTRIELLE (A.M.R.I.), A FRENCH CORPORATION, OF "LAS MERCURIALES", 40, RUE JEAN JAURES, 93176 BAGNOLET CEDEX, FRANCE. Inventors: JEAN CLAUDE GARRIGUES.
RENE I.AULHE.
PIERRE RIEUVERNET.

Application for Patent No. 388/Del/1988 filed on 4-5-1988.

· ·----_

Appropriate office for opposition proceedings (Rule 4, Paten's Rules, 1972) Patent Office Branch, New Delhi-110 005


(Claims 12)

A sealing liner for a closure means for providing sealing upstream/downstream of the closure means, said closure means comprising a closure member (21) movable inside a tubular body (17, 18) said liner comprising:

— two circular substantially concentric scaling elements, namely; a first element (1, 2, 3) providing static scaling and a second element (4, 5, 6) having, on the side opposite the first element (1), a circular scaling surface (11) for cooperating with a circular scaling face in order to provide dynamic scaling;

— a resiliently deformable membrane (14) connecting said elements (1 to 6) sealingly together, and

— a reaction ring (8) applied against the second sealing content (5, 6) opposite said sealing surface (11) to achieve a radially movable assembly distant from the first sealing element (1, 2, 3) characterised in that said second sealing element (4) is provided with a cover (5) forming an annular housing a circular portion of which forms said sealing surface, said housing containing, on the one hand, an annular resiliently deformable bad (6, 7) for acting on said sealing surface (11), and on the other hand, the reaction ring (8) held applied against said bad (7), and in that said housing has two opposite walls (9, 10) so as to provide permanent centering of said bed (7) and said ring (8).



(Complete Specification 16 pages) (drawings 02 sheets).

Ind. Cl.: 170B & D.

Int. C1: C10L 1/10 1/16 1/22. C10M 141/00 169/00.

A PROCESS FOR PRODUCING DISPERSANT-DETERGENT ADDITIVES.

Applicant: EXXON CHEMICAL PATENTS, INC.. a corporation organised and existing under the laws of the S State of Delaware, United States of America, of 1900 East Linden Avenue, Linden, New Jersey 07036, United States of America.

Inventors: MALCOLM WADDOUPS.
BARRY JOHN HOWLETT.

Application for Patent No. 391/Del/1988 filed on 4-5-1988.

Appropriate office for opposition proceedings (Rule 4, Patents Rules, 1972) Patent Office Branch, New Delhi-110 005

(Claims 8)

A process for producing dispersant-detergent additives having improved haze-resistance for use with oleaginous compositions such as herein described which comprises;

(a) contacting a mixture comprising a lubricating oil, an ashless dispersant and a metal detergent such as herein described at a temperature of from 100°C to 160°C for a time of from 1 to 10 hours in the substantial absence of air to form a heat-treated dispersant-detergent-lubricating oil mixture;

(b) cooling said heat-treated mixture to a temperature of not greater (han about 85°C to form a cooled dispersant-detergent-lubricating oil concentrate;

(c) admixing said cooled dispersant-detergent-lubricating oil concentrate with at least one additive selected from the group consisting of copper antioxidant additives and zinc Malkyl dithiophosphate anti-wear additives to form an additive of improved haze-resistance properties, said ashless dispersant comprising a member selected from the group consisting of nitrogen or easter containing dispersants selected from the group consisting of (i) oil souble salts, amides, imides, or izolines and esters such as herein described or misture; thereof, of long chain hyrocarbon substituted mono and idearboxylic acids or their anhydrides; (ii) long about alip's in hydrocarbon having a polyamine attached directy thanco; and (iit) Mannich condensation products a long chain substituted phenol, 1 to 2.5 moles of formaldehyde and 0.5 to 2 moles of polyalkylene polyamine; wherein said long chain hydrocarbon group in (i), (ii) and (iii) is a polymer of a C₂ to C₁₀ mono-olefin, said polymer having an average molecular weight of at least about 1300.

(Complete specification 60 pages) (drawings 03 sheets).

Ind. Cl: 180

172657

Int. Cl.: F 24 C 5/00 5/18

A STOVE.

172656

Applicant: KAMESIIWAR NATH MALLIK, AN INDIAN NATIONAL OF 4/23A, VIKRAM VIHAR, LAJ-PAT NAGAR-IV, NEW DELHI-110 024.

Inventor: KAMESHWAR NATH MALLIK.


Application for Patent No. 394/Del/1988 filed on 05 May 1988.

Appropriate office for opposition proceedings (Rule 4, Patents Rules 1972) Patent Office Branch, New Delhi-110 005.

9 Claims

A stove comprising a tank or cylinder for storage of a fuel, a pump for increasing the pressure within said cylinder to allow a flow of a fuel in a liquiduous state to a regulator assembly, characterized in that a regulator assembly consisting of a pipe having a regulator spindle therewith and being extended into a torturned path so as to form to band pipe connected to said cylinder, a burner assembly consisting of an inlet pipe extended through a burner plate

having a cup surrounding said pipe, a hood provided above said cup and supported on said burner plate, said inlet pipe connected to said regulator assembly through a vaporizer.



Compl. Speen. 13 pages

Drys. 2 Sheets

Ind. Cl.: 157 A-2

172658

Int. Cl. : B 61 L 1/18.

A DEVICE FOR OPERATING A RAILROAD SWITCH.

Applicant: ALSTHOM, A FRENCH, BODY CORPORATE, OF 38 AVENUE KLEBER, 75784 PARIS CEDEX 16, FRANCE.


Inventor: FRANCIS CARMES.

Application for Ptent No. 396/Del/1988 filed on 5 May

Appropriate office for opposition proceedings (Rule 4. Patents Rules 1972) Patent Office Branch, New Delhi-110 005.

7 Claims

A device for operating a railroad switch constituted by two moving blades (1, 2), namely a right point blade and a left point blade, with one of the blades touching and the other blade not touching the associated respective backing rail (3, 4), with at least the touching blade being locked in position, the device comprising a right drive rod (5) persecutively leads (1, 1), the rail (3, 4), with at least the touching blade being locked in position, the device comprising a right drive rod (5) perpendicularly connected to the right point blade (1) in the vicinity of its tip, a left drive rod (6) perpendicularly connected to the left point blade (2) in the vicinity of its tip, and axial drive motor means for said drive rods, wherein the device further comprises a carriage (7) driven in axial translation by said motor means, said carriage (7) being axially movable between a right locking place (12) and a left locking plate (13) which are mutually parallel to the axes of said drive rods (5, 6), said plates (12, 13) being held by a frame, the right drive rod (5) being situated between the right locking plate (12) and said carriage (7) by being at least partially received in a right longitudinal groove (14) of said carriage (7), the left drive rod (6) being situated between the left locking plate (13) and said carriage (7) by being at least partially received in a left longitudinal groove (15) of said carriage, each drive rod being provided with two cylindrical vertical floating pegs (8, 9, 10, 11) extending perpendicularly to said longitudinal grooves (14, 15) and each received in a notch (16, 17, 18, 19) provided in the rod, each, locking plate having at least one vertical locking recess (20) having sloping side walls flaring apart on going from the plate towards the red, and having a depth which is not greater than one-half of the diameter of one of said floating pegs, and wherein the width of said carriage between the two locking plates is stepped over three distinct widths, comprising: at each end, a first step (22A) whose width is not greater than the distance L between the two locking plates less twice the distance P. of a floating pega: followed on such side of diameter D of a floating peg: followed on each sde of the carriage going axially towards the middle of the car-riage by a second step (23A) having a width lying between L-2D and L-D; and finally a central step (24) whose width step; the transition between the first step and the eccond step; the transition between the first step and the eccond step taking place via a sloping wall, and with the distance between the two notches of a drive rod being not less than the length of the central step plus twice the width of a second step, and being not greater than the length of the central step plus the length of a second step plus the length of a first step.



Compl. Specn. 16 pages

Drgs. 8 Sheets

Ind. Cl.: 195 CD

172659

Int. Cl.4: F16 K 5/00.

A WATER TAP.

Applicant: RAJENDRA KUMAR C/O SHRI MANIK CHAND JAI KISHAN, GOLD SMITH, P.O. SASNI, ALI-GARH, UTTAR PRADESH, INDIA, AN INDIAN NA-TIONAL.


Inventor: RAJENDRA KUMAR.

Application for Patent No. 399/Del/88 filed on 6 May

Appropriate office for opposition proceedings (Rule 4, Patents Rules 1972) Patent Office Branch, New Delhi-110 005.

8 Claims

A water tap comprising a main body (6) provided with a passage (9) with an inlet (8) and outlet end (7), an opening (10) being provided for a cock plug (12) rotatably secured with said opening (10) characterized in that a seat (15) being provided with said inlet end of said opening (10), a spring loaded closure (16) coacting with said opening (10) being provided such that in the absence of the cock plug (12) within said opening (10) the spring loaded closure (16) closes said inlet end of said opening (10).



Compl. Specn. 10 pages

Drgs. 2 Sheets

Ind. Cl.: 40 F [IV(1)]

172660

Int. Cl.: B 01 J 8/24

A FLUDIZED BED APPARATUS AND A PROCESS FOR POLYMERIZING AT LEAST ONE ETHYLENI-CALLY UNSATURATED MONIMER IN THE FLUIDIZED BED APPARATUS.

Applicant: BP CHEMICALS LIMITED, OF BELGRAVE HOUSE, 76 BUCKINGHAM PALACE ROAD, LONDON SWIW OSU, ENGLAND, A BRITISH COMPANY.

Inventors: JEAN ALAIN MAUREL, FEDERIC ROBERT MARIE MICHEL MORTEROL, CHARLES RAUFAST.

Application for Patent No. 556/Del/88 filed on 30 June 1988.

Appropriate office for opposition proceedings (Rule 4, Patents Rules 1972) Patent Office Branch, New Delhi-110 005.

10 Claims

A fluidized bed apparatus for use such as polymerisation of ethylenically unsaturated mononers comprising a vessel (1) having the shape of an upright cylinder and a fluidization grid (2) spanning across the vessel along a transverse section of area SI and dividing the interior of said vessel into an upper chamber portion for containing a fluidized bed and a lower gas entry chamber (3) which is closed by a bottom and into which opens at least one fluidizing gas delivery pipe (4), the apparatus being characterised in that a tuyere (5) is positioned in the gas entry chamber (3) to guide fluidizing gas interiorly thereof from the opening of the fluidizing gas delivery pipe (4) to the fluidization grid (2), the tuyere (5) comprising a widening pipe which increases in interior size the wider end (6) of which has an area S2 and is connected to the side wall of the gas entry chamber (3) beneath the fluidization grid (2) and the narrower end (7) of which is positioned in the gas entry chamber (3) farther from the fluidization grid (2) than the flow of gas from the opening of the fluidizing gas delivery pipe (4) through the said narrower end and hence through the interior of said tuyere to the fluidization grid (2) and wherein the area S2 is substantially the same as the area S1 and the ratio of the areas S2/S3 is from 2 to 30.

A process for polymerizing at least one ethylenically unsaturated monomer to produce polymers of ethylene in the fluidzed bed apparatus as claimed in any one of claims 1 to 6, characterized in that it comprises:

- (a) introducing a catalyst of the Ziegler-Natta type or comprising a chromium oxide compound supported on a refractory oxide into the upper chamber portion of the apparatus containing a fluidized bed consisting of a polyolefin powder, at a temperature from 0 to 115°C under a pressure from 0.5 to 5 MPa,
- (b) withdrawing the polymer produced from the fluidized bed apparatus to maintain substantially constant the height of the fluidized bed, and
- (c) introducing a fluidizing gas comprising the ethylenically unsaturated monomer(s) into the entry chamber (3) through at least one delivery pipe (4) and channelling by means of the tuyere (5) essentially into a single upward stream which enters the tuyere through the narrower end (7) with a velocity which is from 2 to 60 times the fluidization velocity in the fluidized bed and which leaves the wider end (6) of the tuyere at a reduced velocity which is from 1.5 to 3 times the fluidization velocity in the fluidization bed thereby obtaining the desired product.

Compl. Specn. 22 pages

Drgs. 2 Sheets

CLAIM UNDER SECTION 20(1) OF THE PATENTS ACT

The claim made by TEMPRA THERM (PTY) LTD, in connection with Patent Application No. 97/Mas/89 (172644) has been allowed.

PRINTED SPECIFICATION PUBLISHED

A limited number of printed copies of the undernoted specification are available for sale from the Patent Office, Calcutta, and its branches at Bombay, Madras and Delhi at two rupees per copy:—

(1)

161038 161039 161040 161041 161042 161043 161044 161045 161046 161047 161048 161049 161050 161051 161052 161053 161054 161055 161056 161057 161058 161059 161060 161061 161062 161063 161064 161065 161066 161067

(2)

 161068
 161069
 161070
 161071
 161072
 161073
 161074
 161075

 161076
 161077
 161078
 161079
 161080
 161081
 161082
 161083

 161084
 161085
 161086
 161087
 161088
 161089
 161090
 161091

 161092
 161093
 161094
 161095
 161095
 161097
 161098
 161099

 161100
 161101
 161102
 161103
 161104
 161105
 161106
 161107

 161108
 161109
 161110
 161111
 161112
 161113
 161114
 161115

 161116
 161117
 161118
 161119
 161120
 161121
 161122

PATENT SEALED ON 01-10-1993

167925 170495*F 1704906*F 170598*D 170615* 170660*
170703*F 170709 170760 170828 170829* 170901 170902*
170903* 170904*D 170906*D 170907*D 170908*D 170910*D
170911* 170915*D 170916*D 170917*D 170918*D 170919*D
170920*D 170952* 170956 170997 170999 171000* 171007*
171013 171018 171026* 171037* 171076*D 171765

Cal-05, Mas-01, Bom-11, & Del-21

*Patent shall be deemed to be endorsed with the words LICENCE OF RIGHT under Section 87 of the Patent Act, 1970 from the date of expiration of three years from the date of sealing.

D-DRUG PATENT, F-FOOD PATENT.

NO PATENT

 160009
 164162
 164176
 164291
 164671
 164942
 166010
 166021

 166060
 166094
 166107
 166146
 166147
 166192
 166202
 166222

 166227
 166241
 166249
 166266
 166274
 166275
 166277
 166278

 166281
 166303
 166308
 166323
 166326
 166335
 166345
 166346

 166348
 166353
 166367
 166372
 166383
 166395
 166396
 166485

 166489
 166493
 166498
 166595
 166556
 166575
 166583

 1666594
 166598
 166601
 166605
 166614
 166615
 166632

REGISTRATION OF ASSIGNMENTS, LICENCES, ETC. (PATENTS)

Assignments, licences or other transaction affecting the interest of the original patentee have been registered in the following cases.

152763 152871 154429 156238 M/s. Lakshmi Machine Works Limited. 156433 157025 157735 159262 159269

151901

152558

160080

AMENDMENT PROCEEDINGS UNDER SECTION 57

Notice is hereby given that Sum tomo Chemical Company a corporation organized under the laws of Japan, of 15 Kitahama 5-Chome, Higash-Ku, Osaka, Japan have made an application under Section 57 of the patents Act, 1970 for amendment of specification of their application for patent No.168916 for process for recovery of gallium by chelate resin.

The application for amendment and the proposed amendments can be inspected free of charge of Patent Office 234/4, Acharya Jagadish Bose Road, Calcutta-700 020 or copies of the same can be had on payment of the usual copying charges. Any person interested in opposing the application for amendment may file a notice of opposition on the prescribed Form 30 within three months from the date of this notification at the Patent Office, Calcutta. If the written statement of opposition is not filed with the notice of opposition it shall left within one month from the date of filing the said notice.

RENEWAL FEES PAID

151951 151962 153164 153165 153499 153533 153712 153724 153749 153943 154229 154278 154445 154469 154802 154867 154901 154903 155483 155491 155697 156480 156523 156645 156935 157081 157117 157611 158198 158317 158379 159097 159583 160110 160851 161393 161552 161557 161608 161638 161723 161776 161961 161981 162144 162306 162369 162485 162487 162585 162589 163309 163356 163380 163532 163748 163867 163898 163969 163966 164117 164329 164340 164644 164834 164866 165049 165202 165288 165413 165416 165429 165709 166410 166616 167076 167351 167380 167657 167728 167921 167928 167989 168119 168250 168263 168385 168505 168944 169079 169432 170019 170171 170610 170672 170722 170726 170728 170728 170795

CESSATION OF PATENTS

 158733
 158772
 158773
 158801
 158805
 158817
 158822
 158834

 158872
 158876
 158880
 158888
 158891
 158933
 158988
 158901

 158903
 158904
 158914
 158921
 158930
 158935
 158943
 158944

 158954
 158961
 158963
 158980
 158986
 158988
 158996
 158999

 159053
 159055
 159069
 159080
 159087
 159096
 159107
 159111

 159114
 159115
 159117
 159138
 159150
 159178
 159189
 159190

 159207
 159228
 159229
 159232
 159245
 159265
 159274

 159279
 159283
 159295
 159296
 159232
 159245
 159265
 159274

RESTORATION PROCEEDINGS

Notice is hereby given that an application for restoration of Patent No. 161638 dated the 15th May, 1985 made by Ruhrtal-Elektizitatsgeseilschaff Hartig GmbH & Co. on the 8th April, 1993 and notified in the Gazette of India, Part III, Section 2, dated the 19th June, 1993 has been allowed and the said patent restored.

Notice is hereby given that an application for restoration of Patent No. 165244 dated the 20th April, 1987 made by E.I. DU Pont De Nemours and company on the 15th March, 1993 and notified in the Gazette of India, Part III, Section 2, dated the 5th June, 1993 has been allowed and the said patent restored.

Notice is hereby given that an application for restoration of Patent No. 166972 dated the 5th May 1987 made by Ion Exchange (India) Limited on the 9th March, 1993 and notified in the Gazette of India, Part III, Section2 dated the 5th June, 1993 has been allowed and the said patent restored.

Notice is hereby given that an application for restoration of Patent No. 167076 dated the 10th April, 1987 made by Westinghouse Electric Corporation on the 7th April, 1993 and notified in the Gazette of India, Part III, Section 2, dated the 19th June, 1993 has been allowed and the said patent restored.

REGISTRATION OF DESIGNS

The following designs have been registered. They are not open to inspection for a period of two years from the date of registration except as provided for in Section 50 of the Designs Act, 1911.

The date shown in the entries is the date of the registration of the design included in the entry.

- Class 1. Nos. 165515 and 165516. Dr. Jose Thaikattil, Physician, University Health Centre, Calicut University P.O., Kerala, India, Indian. "Wick Lamp". April 13, 1993.
- Class 3. No. 165364. Gauri Shankar & Raghuvir Singh, Indian of C-76, Gali No. 8, Braham Puri, Delhi-110053, India. "Children's Multipurpose Seat". February 17, 1993.
- Class 3. No. 165386. Hindustan Lever Ltd. of 165/166, Backbay Reclamation, Bombay-400020, Maharashtra, India. "Bottle". February 26, 1993.
- Class 3. No. 165572. Philippe Charriol of 66, Black's Link, Hong Kong, French citizen. "Writing implement". April 21, 1993.

R. A. ACHARYA.
Controller General of
Patents Designs and
Trade Marks.